

Pietro Fiorentini Governor Line Pressure Regulator Over Pressure Device (DC) Model

The Governor line of gas regulators are designed to comply with the latest CSA and international standards for regulators suitable for indoor and outdoor installations with no modifications. They are ideal for a wide range of residential through large industrial applications. All Governor regulators are equipped with balanced valve design for improved high outlet pressure accuracy regardless of Inlet pressure variation. The double diaphragm with integral vent limiter provides added security. The external vent limiter reduces piping costs and the need for costly vent piping for indoor installations. The number of high capacities and regulator options sometimes eliminates the need for separate units and significantly reduces installation costs.

Additional Information:

- 500 to 1 Turndown
 - Suitable for use with Natural Gas, LPG, and other non-corrosive clean gas
 - Inlet Pressure: 3 PSIG to 10 PSIG
 - Max. Inlet 10 PSIG for CSA and non-CSA applications
 - Outlet pressure: 2" W.C. to 1 PSIG for CSA and up to 3 PSIG for non-CSA applications
 - Temperature range: -40°F to 150°F
 - Connections: 1/2" thru 4"
 - Maximum Emergency Inlet Exposure Pressure: 80 PSIG
 - Suitable for Indoor or Outdoor Installation
-

Pietro Fiorentini Governor Line Pressure Regulators

The Governor line of gas regulators are designed to comply with the latest CSA and international standards for regulators suitable for indoor and outdoor installations with no modifications. They are ideal for a wide range of residential through large industrial applications. All Governor regulators are equipped with balanced valve design for improved high outlet pressure accuracy regardless of inlet pressure variation. The double diaphragm with integral vent limiter provides added security. The external vent limiter reduces piping costs and the need for costly vent piping for indoor installations.

Additional Information

- Suitable for use with Natural Gas, LPG, and other non-corrosive clean gas
 - Inlet Pressure: 3" W.C. to 2 PSIG CSA approved SA Appr
 - Max. Inlet 7.25 PSIG for non-CSA applications
 - Outlet pressure: 2" W.C. to 14" W.C. and up to 4.25 PSIG for non-CSA applications
 - Temperature range: -40°F to 150°F
 - Connections: 1/2" thru 4"
 - Maximum Emergency Inlet Exposure Pressure: 80 PSIG
 - Suitable for Indoor or Outdoor Installation
-

Pietro Fiorentini Norval Pressure Regulator

Norval pressure regulators are direct acting devices for low and medium pressure applications, controlled by a diaphragm and counter spring. These regulators are suitable for use with previously filtered, non-corrosive gases and Bio Gas, depending upon its composition. The modular design of the Norval pressure regulator allows the addition of a slam shut device for use as an "in-line monitor" installed in the same body, without changing the face-to-face dimensions.